

Month 11: First border & Flange (provided October 2017; share November 2017)

Fabric needed: Cut the listed pieces for each fabric.

	3" blocks on-point	9" block	9" blocks on-point
Fabric 4	2 - 1" x 14-7/8" 2 - 1" x 19-3/4"	4 - 1-1/4" x 33-1/2"	2 - 1-1/4" x 44-1/2" 2 - 1-1/4" x 59-3/8"
Fabric 5	2- 1-1/4" x 19-3/4" 2 - 1-1/4" x 16-3/8"	2 - 2" x 33-1/2" 2 - 2" x 36-1/2"	2 - 2" x 59-3/8" 2 - 2" x 47-1/2"

Instructions

Note: Watch carefully as you stitch.

1. Carefully press the Fabric 4 strips in half, lengthwise, wrong sides together to prepare the flange.
2. Baste each flange piece to the right side of the quilt center.
 - a) Pin a flange edge to an edge of the quilt center of the same length.
 - b) Using a slightly longer stitch length, stitch inside the seam allowance to baste the flange piece in place.
3. Sew the Fabric 5 side borders in place, catching the flange in the seam. Press the seam toward the added border.
4. Sew the Fabric 5 top and bottom borders in place as in Step 3.
5. The quilt should now measure 36-1/2" x 36-1/2" for 9" blocks or 47-1/2" x 62-3/8" for 9" blocks on-point. (16-3/8" x 21" for 3: blocks on-point)